

SAFETY DATA SHEET

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
June 1, 2015
Page 1 of 8

1. Identification of the Preparation and of The Company

Product Name and/or code: MICHAEL HARDING ARTIST OIL COLORS - COLORS CONTAINING HEXAVALENT CHROMIUM
Effective Date: 1-Jun-15
Manufacturer: Michael Harding Art Materials Ltd.
36 Springdale Industrial Estate
Cwmbran, Gwent NP44 -5BD, Wales
Information Contact: North America: 978-549-4029
UK/Europe: 44 (0) 1633 - 484-700
Emergency Contact: Contact your local Poison Control Center
Product Use: ART MATERIAL - Consumer Product

2. Hazards Identification

Information pertaining to particular dangers for man and environment. This product has been classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Emergency Overview

WARNING! HARMFUL IF SWALLOWED.Cancer Hazard from inhaled dust. KEEP OUT OF REACH OF CHILDREN

Label Elements

Pictograms

Conforms to ASTM D-4236



GHS 08

GHS 07

Signal Word

WARNING!

Hazard Statement

HARMFUL IF SWALLOWED.Cancer Hazard from inhaled dust. Do not spray apply.

Precaution Statement

Do not eat, drink or smoke while using. Dust is an irritant. Avoid all contact. Wear protective gloves and clothing. Avoid creating dust. Do not sand dry film. Provide good ventilation.Wash hands and face before eating or smoking.

Children's Statement

KEEP OUT OF REACH OF CHILDREN.

NFPA

Health 2-Warning.Maybe harmful if inhaled or swallowed.

Flammability 1 - Combustible if heated

Reactivity 0 - Stable

HMIS

Health 2 - Moderate Hazard

Flammability 1 -Slight Hazard

Physical Hazard 0 - Minimal Hazard

Regulation (EC) No. 1272/2008

Hexavalent chromium compounds are classified in the Annex I of the regulation.

Export and Import of Dangerous Chemicals Regulation (EC)No. 649/2012

This product and its ingredients are listed in the Annex I of the regulation.



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
 June 1, 2015
 Page 3 of 8

7. Handling and Storage

Safe Handling

Use under ventilated conditions. Avoid eye contact. For personal protection, we recommend that employees wash thoroughly after handling product. Always wash before eating, smoking or using toilet facilities. Keep container closed when not in use.

Storage

Keep the sample in a cool dry ventilated area. Keep away from fire and heating sources.

8. Exposure Controls/Personal Protection

Personal Protective Equipment

Wear safety goggles and protective gloves to avoid dust contact.

Exposure Limits

The following information refers to Barium chromate.

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Barium chromate	10294-40-3	TWA	0.500000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
	Remarks	See Table Z-2 for the exposure limit for any operations or sectors where the exposure limit in § 1910.1026 is stayed or is otherwise not in effect Substance listed; for more information see OSHA document 1910.1026		
		TWA	0.500000 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Eye, skin, & Gastrointestinal irritation Muscular stimulation Not classifiable as a human carcinogen		
		TWA	0.500000 mg/m3	USA. NIOSH Recommended Exposure Limits
		TWA	1.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		CEIL	1.000000mg/10 m3	USA. Occupational Exposure Limits (OSHA) - Table Z-2
		Z37.7-1971 This standard applies to any operations or sectors for which the exposure limit in the Chromium (VI) standard, Sec. 1910.1026, is stayed or is otherwise not in effect.		
		PEL	0.005000 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens
		1910.1026 This standard applies to occupational exposures to chromium (VI) in all forms and compounds in general industry, except: (a) Exposures that occur in the application of pesticides regulated by the Environmental Protection Agency or another Federal government agency (e.g., the treatment of wood with preservatives); (b) Exposures to portland cement; or (c) Where the employer has objective data demonstrating that a material containing chromium or a specific process, operation, or activity involving chromium cannot release dusts, fumes, or mists of chromium (VI) in concentrations at or above 0.5 µgm/m3 as an 8-hour time-weighted average (TWA) under any expected conditions of use. Chromium (VI) [hexavalent chromium or Cr(VI)] means chromium with a valence of positive six, in any form and in any compound OSHA specifically regulated carcinogen		



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
 June 1, 2015
 Page 4 of 8

		PEL	0.005000 mg/m ³	OSHA Specifically Regulated Chemicals/Carcinogens
		1910.1026 This standard applies to occupational exposures to chromium (VI) in all forms and compounds in general industry, except: (a) Exposures that occur in the application of pesticides regulated by the Environmental Protection Agency or another Federal government agency (e.g., the treatment of wood with preservatives); (b) Exposures to portland cement; or (c) Where the employer has objective data demonstrating that a material containing chromium or a specific process, operation, or activity involving chromium cannot release dusts, fumes, or mists of chromium (VI) in concentrations at or above 0.5 µg/m ³ as an 8-hour time-weighted average (TWA) under any expected conditions of use. Chromium (VI) [hexavalent chromium or Cr(VI)] means chromium with a valence of positive six, in any form and in any compound OSHA specifically regulated carcinogen		
		TWA	0.000200 mg/m ³	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen See Appendix C See Appendix A		

Respiratory and Ventilation

Wear approved NIOSH/MSHA respirator if exposure to mist or vapor exceed applicable PEL/TLV limits. Use in accordance with manufacturer's use limitations and OSHA STANDARD 1910-34. Local ventilation may be used to prevent routine inhalation.

Skin Protection

Handle with non-porous nitrile gloves. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full Contact Material: Nitrile rubber
 Minimum layer thickness: 0.11 mm Break through time: 480 min
 Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)
 Splash protection Material: Nitrile rubber
 Minimum layer thickness: 0.11 mm Break through time: 480 min
 Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)
 Data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374
 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye Protection

Safety glasses conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

9. Physical and Chemical Properties

Appearance

Viscous colored oil paints



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
June 1, 2015
Page 5 of 8

Physical State	Solid - Paste
Color	See product list in Section 16
Odor	Slightly aromatic.
Boiling Point	Greater than 100°C/ 212°F Greater than 100°C/ 212°F Greater than 100°C/ 212°F Greater than 100°C/ 212°F Greater than 100°C/ 212°F
Freezing Point	Not applicable
State (pH)	8.5 - 9.2
Specific Gravity	1.0 - 2.0
Viscosity	Not determined (Viscous material)
Flashpoint	Greater than 230°C/ 446°F
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Solubility in water	Not miscible

10. Stability and Reactivity

Reactivity:	Reaction with reducing agents.
Chemical Stability	Stable
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatible materials	Combustible material (eg. Cotton)
Hazardous Decomposition Products	No information available.

11. Toxicological Information

Health Effects	Studies have not been performed on this particular mixture. The information below is based on data on the individual ingredients.
Oral	Expected to be greater than 2,000 mg/kg (rats)
Ingestion	Nausea, vomiting and abdominal pain.
Inhalation	This product poses no inhalation risk.
Dermal	Not a skin sensitizer.
Eye Effects	May cause irritation

12. Ecological Information

Toxicity:	Very toxic to aquatic organisms.
Aquatic toxicity	Very toxic to aquatic organisms.
Persistence and degradability	A mixture of biodegradable and non biodegradable ingredients. No other information is available.
Bio accumulative potential	Not expected to bioaccumulate significantly.
Mobility in soil	The product has poor water-solubility.
Additional ecological information	No information available.

13. Disposal Considerations

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Contact specialist disposal companies. Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
June 1, 2015
Page 6 of 8

14. Transport Information

The following transportation categories do not apply to this mixture sold as a consumer use product (non-bulk). The information below refers to the classification of Barium chromate.

DOT Non-Bulk

Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Technical Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Hazard Class	5.1
UN Number	1479
Packing Group	II

IMDG

Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Technical Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Hazard Class	5.1
UN Number	1479
Packing Group	II
EmS Number	F-A, S-Q
Marine Pollutant	Yes

ICAO/IATA

Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Technical Shipping Name	Oxidizing solid, n.o.s. (Barium chromate)
Hazard Class	5.1
UN Number	1479
Packing Group	II

Michael Harding Art Materials Ltd. are IATA certified through the UK CAA.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the materials.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture.

SARA	Not applicable
Section 355 (extremely hazardous substances)	Not applicable
Section 313 (Specific toxic chemical listing)	Barium chromate (CAS: 10294-40-3)

TSCA (Toxic Substance Control Act)	All ingredients are listed.
<i>The Safe Drinking Water and Toxic Enforcement Act of 1986 - California Proposition 65</i>	As of June 1, 2015 this product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
Chemicals known to cause cancer	Barium chromate (CAS: 10294-40-3)
Chemicals known to cause reproductive toxicity for females	Barium chromate (CAS: 10294-40-3)
Chemicals known to cause reproductive toxicity for males	Barium chromate (CAS: 10294-40-3)



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
June 1, 2015
Page 7 of 8

Chemicals known to cause developmental toxicity Barium chromate (CAS: 10294-40-3)

Carcinogenicity categories

EPA (Environmental Protection Agency) Not applicable to this mixture.

TLV (Threshold Limit Value established by ACGIH) Not applicable to this mixture.

MAK (German Maximum Workplace Concentration) Not applicable to this mixture.

NOISH-Ca (National Institute for Occupational Safety & Health) Not applicable to this mixture.

OSHA-Ca (Occupational Safety & Health Administration) Not applicable to this mixture.

16. Other Information

Product Number and Color Name	Pigment Identification
108 Lemon Yellow	PY 31 Barium Chromate

Hazard statement(s)

H272 May intensify fire; oxidiser.
H302 + H332 Harmful if swallowed or if inhaled
H350 May cause cancer.

Precautionary statement(s)

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat.
P220 Keep/Store away from clothing/ combustible materials.
P221 Take any precaution to avoid mixing with combustibles.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.



SAFETY DATA SHEET
MICHAEL HARDING ARTIST OIL COLORS
COLORS CONTAINING HEXAVALENT CHROMIUM

HAR1490
June 1, 2015
Page 8 of 8

Reason for Issue:

GHS Format

Prepared by:

Rudolph J. Jaeger, Ph.D., DABT, ERT (UK)
Chief Toxicologist and President
ENVIRONMENTAL MEDICINE, INC.
263 CENTER AVENUE
WESTWOOD, NJ 07675
jaegerr@envmed.com
201-666-7929 x13

The information contained in this Safety Data Sheet was compiled using the latest and most reliable information available to Michael Harding Art Materials, Ltd. The information is provided without any warranty, express or implied regarding its correctness or accuracy nor will Michael Harding Art Materials Ltd. assume any liability for any loss or damage arising out of the use of this information including without limitation direct or indirect losses or expenses. To the extent permitted by law, no warranty express or implied regarding the product described herein shall be created by or inferred from any state or omission for this SDS. It is solely the responsibility of the user to determine safe conditions for use of this product and to assume liability for any loss, damage or expense whatsoever arising out of the product's improper use.