

# deffner & Johann

Supplies for RESTORATION | CONSERVATION | ART HANDLING – SINCE 1880

## TECHNICAL DATA SHEET

[info@deffner-johann.de](mailto:info@deffner-johann.de) | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

## Lascaux Acrylic Transparent Varnish 2-UV matt

For the ideal finishing treatment of a work: acrylic varnishes increase resistance to the effects of weather, soiling and mechanical stress and make cleaning easier. They have good adhesive properties, are non-yellowing, lightfast and age-resistant. A final varnish can harmonize surface sheen in a painting.

### Composition

Pure acrylic resin dispersion with ultraviolet (UV) light stabilizers

### Properties

- water-thinnable
- clear protective varnish for optimizing colour stability and resistance to weathering in acrylic colours
- built-in UV protection stabilizes the system in the short-wave UV range
- lightfast, age resistant and waterproof

### Applications

- the lightfastness of the less-resistant yellow, red and yellow-green Lascaux Acrylic Studio Colours can be stabilized by applying a final protective coat of Lascaux Acrylic Transparent Varnish-UV for outside work
- suitable for use on Lascaux Studio Metallic acrylic colours 990, 991, 992, 993 and 994 in interiors

### Directions

Preparation and use of Lascaux Acrylic Transparent Varnish-UV is the same as for the standard version, with the following reservations: At least two thin coats are always required, each diluted with about 25% of water, to guarantee the necessary UV absorption effect. Types 2 and 3 need to be shaken or stirred before use. Allow about 4-6 hours drying time between coats. Protection against UV rays is only achieved by applying Lascaux Acrylic Transparent Varnish-UV as the final stage. Mixing the product with the paints has no effect. Naturally, Lascaux Acrylic Transparent Varnish-UV can also be used for interior work but this is not strictly necessary.

### Special Notes

See chapter Transparent Varnishes

### Coverage

Approx 40-70 ml/m<sup>2</sup> per coat, depending on the support and application.

### Notes

Acrylic Transparent Varnish 1-UV gloss and 2-UV matt contain UV absorbers that confer stability against UV rays. USA: conforms to ASTM D-4236. "Non toxic".

### Sizes

Art. Nr. 2026025: 250 ml

Art. Nr. 2026100: 1 l

Art. Nr. 2026500: 5 l