

# deffner & Johann

Supplies for RESTORATION | CONSERVATION | ART HANDLING – SINCE 1880

## TECHNICAL DATA SHEET

[info@deffner-johann.de](mailto:info@deffner-johann.de) | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

## Lascaux Acrylic Sizing

For the best treatment of varied surface preparations we offer compatible sizing. A comprehensive variety suitable for all types of substrates, including paper, textiles, wood, etc. For both interior and exterior use.

## Lascaux Sizing

### Composition

Pure acrylic resin dispersion stabilized with special protective colloids.

### Properties

- thinnable with water
- flexible
- colourless
- lightfast and age resistant

### Applications

- sealing with Lascaux Sizing increases the bonding of the following primer
- minimizes the penetration of the priming and paint layers to the back of the canvas
- makes the canvas impervious before applying primer

### Directions

For best results, the canvas should be mounted taut on the stretcher bars.

For use with a brush, dilute Lascaux Sizing with the same amount of water and apply evenly. Take care that it does not sink through the canvas. Lascaux Sizing may be applied undiluted with a palette knife.

The canvas may sag when the Sizing is dry, even though it was stretched taut while drying. This depends on the weight and weave of the canvas. In such cases, it is best to re-stretch the canvas before priming it.

Priming the canvas: when used on fibrous supports, the sizing should be left until it is completely dry and then rubbed down with very fine sandpaper or a pumice stone.

Acrylic primers such as Lascaux Primer, Lascaux Gesso or Lascaux Structura are ideal for acrylic, oil and watercolour painting. These age-resistant products will not become brittle. They are applied evenly with a soft brush in several coats, thinned with about 10-30% water, or undiluted with a palette knife.

Lascaux Sizing should not be used below the temperature of +8°C (+46°F).

### Coverage

Approx. 80 ml/m<sup>2</sup> per coat, depending on the support and application.

### Notes

USA: conforms to ASTM D-4236.

### Sizes

Art. Nr. 2027005: 500 ml

Art. Nr. 2027010: 1l.

Art. Nr. 2027050: 5l.