

SAFETY DATA SHEET

info@deffner-johann.de | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lascaux Acrylic Transparent Varnish 3 UV

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses

Acrylic Transparent Varnish with UV protection

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier : Lascaux Colours & Restauro, Barbara Diethelm AG

Street : Zürichstrasse 42

Postal code/city : CH-8306 Brüttisellen

Telephone : +41 44 807 41 41

Telefax : +41 44 807 41 40

Information contact : info@lascaux.ch

European address : Lascaux Colours & Restauro Europe GmbH

Street : Turmstrasse 11

Postal code/city : D-78467 Konstanz

Telephone : +49 7531 911 3996

Telefax : +49 7531 911 3997

Information contact : info@lascaux.de

1.4 Emergency telephone number

Tox Info Suisse, 24-h-emergency number 145, Tel. +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

BENZOTRIAZOL-DERIVAT ; CAS No. : 104810-47-1

BENZOTRIAZOL-DERIVAT ; CAS No. : 104810-48-2

1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P261	Avoid breathing spray mist and sanding dust.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to an authorised waste collection point.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

BENZOTRIAZOL-DERIVAT ; CAS No. : 104810-48-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

BENZOTRIAZOL-DERIVAT ; CAS No. : 104810-47-1

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

1,2-BENZISOTHIAZOL-3(2H)-ONE ; EC No. : 220-120-9; CAS No. : 2634-33-5

Weight fraction : $\geq 0,005 - < 0,05 \%$

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Following inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

In case of skin contact

Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

5.4 Additional information

Do not allow the quenching water into the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources and provide for good ventilation. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

No particular measures required.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (D) : 12

Storage class (TRGS 510) (D) : 12

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep containers dry and cool. Comply with the health and safety at work laws.

7.3 Specific end use(s)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

POLYETHYLENE GLYKOLS 200 - 400 ; CAS No. : 25322-68-3

Limit value type (country of origin) : MAK (CH)

Limit value : 1000 mg/m³

Remark : SSC

Version : 01.01.2013

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 1000 mg/m³

Peak limitation : 8(II)

Remark : Y

Version : 04.11.2017

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Wear protective glasses in case of splashes.

Skin protection

Body protection

After skin contact wash thoroughly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Milky.

Odour

Poor, characteristic.

Safety relevant basis data

Initial boiling point and boiling range :	(1013 hPa)	approx.	100	°C
Flash point :			not applicable	
Vapour pressure :	(50 °C)	approx.	120	hPa
Density :	(20 °C)	approx.	1,0	g/cm ³
pH :		approx.	7,0 – 8,0	
Viscosity :	(20 °C)	approx.	100 - 1000	mPa.s

9.2 Other information

None

SECTION 10: Stability and reactivity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

No information available.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

There are no data available on the product itself. Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

SECTION 14: Transport information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Acrylic Transparent Varnish 3 UV**
Revision date : 19.04.2017 Version (Revision) : 4.1.0 (4.0.0)
Print date : 25.04.2017

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

U.S.A. Conforms to ASTM D-4236.

Technische Anleitung Luft (TA-Luft) (D) :

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class (D) : 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lascaux Acrylic Transparent Varnish 3 UV
Revision date : 19.04.2017 **Version (Revision) :** 4.1.0 (4.0.0)
Print date : 25.04.2017

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
