

# deffner & Johann

Supplies for RESTORATION | CONSERVATION | ART HANDLING – SINCE 1880

## TECHNICAL DATA SHEET

[info@deffner-johann.de](mailto:info@deffner-johann.de) | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

## Lascaux Fixativ

Lascaux Fixativ(solvent based)

### Composition

Pure acrylic resin in organic solvents

### Properties

- extremely lightfast and age resistant
- non-matt
- permits invisible fixing on absorbent supports(paper, cardboard, etc.)
- a silky-matt to a slightly glossy varnish can be obtained on non-absorbent substrates (prints, photographs, acrylic colours and oil paintings)
- it is non-yellowing
- does not change the hue of colours upon drying

### Applications

- a multi-purpose fixative which seals or fixes almost any product on almost any surface
- for invisible fixing of drawings in pencil, charcoal, pastel and wax crayons, particularly on delicate paper
- can be applied as a fixative or a waterproof sealing coat to water-colours, India ink or tempera works
- sealing with Lascaux Fixativ makes photographs, photostats, art prints, lithographs, proofs, press-on lettering and gold leaf scratch proof
- suitable as a final varnish for acrylic colours and thoroughly dried out oil paintings, etc.
- whose high quality has been tried and tested in many fields including art teaching, graphic and fine art, printing, bookbinding and architectural draftsmanship

### Directions

Apply a thin, even layer from a distance of 30 cm. Avoid wetting or dampening. Let dry thoroughly. Repeat procedure and apply multiple thin layers until the desired level of fixation is obtained.

As a varnish for acrylic paintings, Lascaux Fixative should be applied in multiple layers in order to obtain an even satin finish.

### Notes

Lascaux Fixativ contains organic solvents. It is labeled with the symbols "F+" - Extremely flammable and "Xi" - irritant. Do not breathe spray and vapor. Use only in well ventilated areas. Keep from heat and direct sunlight. Keep away from sources of ignition. Do not smoke. Keep out of reach of children. USA: conforms to ASTM D-4236. "Non toxic".

### Sizes

Art. Nr. 2030030: Spray cans containing 300ml (12,5 fl. ounces, 217g),

Art. Nr. 2030100: 1 l. (for use with spray gun).