

TECHNICAL DATA SHEET

info@deffner-johann.de | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.



Lascaux Modelling Paste B

A differentiated and comprehensive assortment of 12 opaque, ready-to-use modelling pastes available in a variety of textures:

Modelling Paste A
Grain A = smooth
Grain B = coarse

Colours: Colours:

Natural = neutral Natural = neutral

Composition

Thickened pure acrylic resin dispersion with highgrade calcite filler, finely ground. Modelling Pastes B contain quartz sand additionally.

Properties

- · flexible, elastic hard
- · have excellent adhesion properties
- · do not crack in thicker layers
- · are waterproof once dry and can be over painted
- · Modelling Paste A: dry to a smooth surface
- Modelling Paste B: dry to a rough surface

Applications

- · relief-type applications
- for impasto painting: gives paint more body and extends paint volume
- · use in collage and mosaics for imbedding materials
- for use in texturing grounds (fresco like) or substrates
- · restoration work

Directions

Modelling Pastes are used undiluted in any final layer thickness. However, the paste should never be applied in layers of more than 1 cm (2/5") at a time in order to keep drying times reasonably short. When completely dry, layers can be covered with more paste or painted with acrylics as desired. A certain amount of shrinkage takes place due to evaporation as the paste dries, but there is no crack formation.

Modelling Pastes can also be added to Lascaux Acrylic colours in any ratio for impasto painting. When mixing colours with the various Natural Modelling Pastes, colours will hardly be altered.

The paste gives a slight body to transparent washes. The strongest modelling effect is obtained by applying

the paste unmixed and overpainting with Lascaux Acrylic colours when dry.

Fabric, stones, wood, bits of metal and other materials can be embedded in the paste for collages. The powerful grip of the acrylic base provides an excellent anchorage. In restoration work, Modelling Pastes can be used to supplement impasto, relief, fresco plaster or for stopping cracks.

Modelling Pastes B is suitable for fresco-type priming on virtually all supports. Mixed with Lascaux Primer, it gives a fine grainy surface that is easy to paint.

Notes

USA: conforms to ASTM D-4236.

Sizes

Art.Nr. 2039050: 500 ml Art.Nr. 2039100: 1 l. Art.Nr. 2039500: 5 l.

deffner & Johann

Directions

As a painting ground Structura can be applied, directly or diluted with water, in several layers; also in mixtures with Lascaux Primer, Gesso or Studio White, depending on the desired absorption and texture. Supports which are very absorbent should first be impregnated; with Lascaux Medium 1, Acryl Transparent Varnish 1 gloss or Hydro-Sealer (approx. diluted 1:4 with water). Heavy impastos should be built in several layers to reduce the drying time.

Structura Natural can be mixed with all Lascaux colours; due to its minimal tinting strength the hues will hardly be altered. Thanks to the fine texture the intensity of the colours will be enhanced. This is especially apparent in mixtures with Lascaux Aquacryl colours, as well as with glazes on Structura grounds.

Finished works can be varnished for protection with Lascaux Transparent Varnish.

Notes

USA: conforms to ASTM D-4236.

Sizes

Jars of 250 ml and 1l. Buckets of 5 l. Natural is also available in jars of 500 ml.