

TECHNICAL DATA SHEET

info@deffner-johann.de | +49 (0)9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

Lascaux Acrylic Adhesive 498 20-X

Base

Type 498 20-X contains 20% Xylol, have a pH 8-9 and is biocide stabilized.

Filmproperties

	498 20-X
Minimum film formation temp. (MFT):	approx. 5°C
Glass transition temperature:	approx. 13°C
Elongation at break:	approx. 400%
Dry film:	elastic hard, tack-free, clear
Minimum sealing temperature:	68-76°C

Solubility

Water-dilutable, insoluble in water after drying.

498 20-X: dissolve well in acetone, ethanol, toluene, xylene. Insoluble in white spirit.

Applications

For light-resistant, non-ageing, non-crosslinking linings, marouflages, laminations, collages etc. For wet application or reactivation of dry film, on absorbent and non-absorbent supports such as paper and cardboard, textiles, wood- and fibreplates, polyesterplates, plaster and concrete, glass and acrylic glass, aluminium etc.

Lascaux Acrylic Adhesive 498 20-X is especially suited for strip-lining, fabric marouflages and mounting.

Safety

Please observe safety information on the safety data sheet.

Storage

Keep containers closed, when not using the product. Store at constant temperature between 5°C and 25°C.

Sizes

Art.Nr.: 2051100: 1 l

Art.Nr.: 2051500: 5 l