

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 064 - Dammar varnish, mat

1/9 Version 5.1 ( 09.12.20 ) Page

### SECTION 1: Identification of the substance/mixture and of the

## company/undertaking

### 1.1 Product identifier

Article No.

50 064 - Dammar varnish, mat **Trade name** 

50064

**Name INCI** Name Ph. Eur. **REACH registration No.** 

UFI: U7NF-D469-E00G-KN0U

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**General use** 

Products for creation of art.

Uses advised against

### 1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG

Otto-Hahn-Strasse 2 D-40699 Erkrath

Tel +49 (0) 211 - 2509 - 0 Fax +49 (0) 211 - 2509 - 479

info@schmincke.de www.schmincke.de Schmincke-lab:

mo-th 8.00-16.30, fr 8.00-13.30 tel. +49 (0) 211-2509-474 labor@schmincke.de

### 1.4 Emergency telephone number

**Emergency Emergencycall Berlin** Information +49 30-30686700

(24/7 counseling in german and english)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

Flam. Liq. 3; H226 Flammable liquid and vapour. STOT SE 3; H335 May cause respiratory irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

### 2.2 Label elements

### Labelling









09.12.20

Issue date:

Signal word Danger

**Hazard statements** 

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 064 - Dammar varnish, mat

 Article No.
 50064
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 2/ 9

H411 Toxic to aquatic life with long lasting effects.

Safety precautions

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/.. P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/or shower.

**Hazard components for labelling** 

Text for labelling (CLP)

Repeated exposure may cause skin dryness or cracking. (EUH066)

### 2.3 Other hazards

# SECTION 3: Composition / information on ingredients

### 3.1 Substances

#### **Chemical characterisation**

White spirit
Dammar resin
wax
CAS-Number
EINECS / ELINCS / NLP
EU index number

Customs tariff number REACH registration No.

RTECS-no. Hazchem-Code CI-Number

### 3.2 Mixtures

#### Substance 1

solvent naphtha (petroleum), light, aromatic: 50 - <75%

CAS: 64742-95-6

REACH: 01-2119455851-35

Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / -; EUH066 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3;

H336

**Additional information** 

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

### **General information**

If you feel unwell, seek medical advice (show the label where possible).

### In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

according to Regulation (EC) No. 1907/2006 (REACH)

# 50 064 - Dammar varnish, mat

 Article No.
 50064
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 3/ 9

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eve contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 - 15 minutes. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Immediately get medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

### 4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

#### 5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

**Additional information** 

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

### **6.2 environmental precautions**

Discharge into the environment must be avoided.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

**Additional information** 

### 6.4 Reference to other sections

Dispose of waste according to applicable legislation.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

#### Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

### Precautions against fire and explosion

No special measures are required.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Hints on joint storage

Storage class

**Further details** 

Protect from frost and exposure to sun.

### 7.3 Specific end use(s)

according to Regulation (EC) No. 1907/2006 (REACH)

# 50 064 - Dammar varnish, mat

50064 09.12.20 Article No. **Issue date:** 5.1 ( 09.12.20 ) 4/9 Version Page

### **SECTION 8: Exposure controls/personal protection**

#### **8.1 Control parameters**

64742-95-6 solvent naphtha (petroleum), light, aromatic

DEU	WEL	50,000	mg/m³	2(II); AGS

#### **DNEL overview**

64742-95-6 solvent naphtha (petroleum), light, aromatic

DNEL worker	Long-term - inhalation, system	150,00000	mg/m³
DNEL worker	DNEL worker Long-term - dermal, local effe		mg/kg bw/day
DNEL Consumer	Long-term - oral, systemic eff	11,00000	mg/kg bw/day
DNEL Consumer	Long-term - inhalation, system	32,00000	mg/m³
DNEL Consumer	Long-term - dermal, systemic e	11,00000	mg/kg bw/day

### 8.2 Exposure controls

### Occupational exposure controls

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection must be worn whenever the WEL levels have been exceeded.

Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

### **Hand protection**

Qualified materials: Nitrile rubber Layer thickness > 0,35 mm Breakthrough time > 480 min

Ultranitril 492 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

#### Eye protection

Goggles

### **Body protection**

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

#### General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

### **SECTION 9: Physical and chemical properties**

#### 9.1 information on basic physical and chemical properties

liauid **Form** 

yellowish, cloudy Colour weak aromatic Odour

> min max

Initial boiling point and

boiling range

Melting point/freezing point

 $\sim 40$  °C Flash point/flash point range

**Flammability** 

**Ignition temperature** 

Auto-ignition temperature

**Explosion limits** Refraction index

Viscosity

10 mm<sup>2</sup>/s 40 °C 12 mm<sup>2</sup>/s Viscosity

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 064 - Dammar varnish, mat

Article No. 50064 Issue date: 09.12.20
Version 5.1 ( 09.12.20 ) Page 5/ 9

Vapour pressure
Density
O,84 g/ml
20 °C
Partition coefficient: n-octanol/water

Danger of explosion

### 9.2 Other information

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Product is stable under normal storage conditions.

**10.2 Chemical stability** 

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

#### 10.5 Incompatible materials

strong oxidizing agents

### 10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### **Toxicological tests**

64742-95-6 solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,00000	mg/kg	-
inhalative	LC50	Rat	>	10,20000	mg/L	(4h)
dermal	LD50	Rat	>	2000,00000	mg/kg	-

#### **Acute toxicity**

No data available

In case of inhalation

No data available

After swallowing

No data available

In case of skin contact

No data available

After eye contact

No data available

### **Practical experience**

**General remarks** 

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Ecotoxicological effects**

64742-95-6 solvent naphtha (petroleum), light, aromatic

LC50	fish		9,20000	mg/L	(96h)
EC50	Algae	>	2,60000	mg/L	(72h)

according to Regulation (EC) No. 1907/2006 (REACH)

## 50 064 - Dammar varnish, mat

 Article No.
 50064
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 6/ 9

EC50 Daphnia magna (Big water flea) 3,20000 mg/L (48h)

**Aquatic toxicity** 

No data available

Water Hazard Class 2

WGK catalog number General information

### 12.2 Persistence and degradability

**Further details** 

Product is partially biodegradable.

Oxygen demand

### 12.3 Bioaccumulative potential

Bioconcentration factor (BCF)
Partition coefficient: n-octanol/water

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

**General information** 

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

### **Product**

Waste key number

080111\* waste paint and varnish containing organic solvents or other dangerous substances

Recommendation

#### Contaminated packaging

Waste key number

Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### **Additional information**

# **SECTION 14: Transport information**

### **14.1 UN number**

1263

#### 14.2 UN proper shipping name

ADR, ADN Paint related material IMDG, IATA PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

**ADR, ADN** 3 **IMDG** 3 **IATA** 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Marine Pollutant - IMDG

according to Regulation (EC) No. 1907/2006 (REACH)

# 50 064 - Dammar varnish, mat

 Article No.
 50064
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 7/ 9

Marine Pollutant - ADN Yes

### 14.6 Special precautions for user

### Land transport (ADR/RID)

Code: ADR/RID F1
Kemmler-number 30
Hazard label ADR 3
Limited quantities 5L

Contaminated packaging: Instructions P001 - IBC03 - LP01 - R001

Contaminated packaging: Special provisionsPP1Special provisions for packing togetherMP19Portable tanks: InstructionsT2Portable tanks: Special provisionsTP1 - TP29Tank codingLGBFTunnel restrictionD/E

Remarks

**EO** E1

**Special provisions** 163 - 367 - 650

#### Sea transport (IMDG)

**EmS** F-E, S-E

**Special provisions** 163 - 223 - 367 - 955

Limited quantities 5L

Contaminated packaging: Instructions P001 - LP01
Contaminated packaging: Special provisions PP1
IBC: Instructions IBC03

 IBC: Provisions

 Tank instructions IMO

 Tank instructions UN
 T2

 Tank instructions Special provisions
 TP1 - TP29

Stowage and segregation

Properties and observations

Remarks

**EQ** E1

### **Air transport (IATA-DGR)**

 Hazard
 Flammable Liquid

 Passenger
 355 (60L)

 Passenger LQ
 Y344 (10L)

 Cargo
 366 (220L)

 ERG
 3L

Remarks

EQ E1 Special Provisioning A192

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

category A

### **National regulations**

### **Europe**

Contents of VOC [%]
Contents of VOC

[g/L]

Further regulations, limitations and legal requirements

according to Regulation (EC) No. 1907/2006 (REACH)

# 50 064 - Dammar varnish, mat

 Article No.
 50064
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 8/ 9

#### Germany

Storage class

Water Hazard Class 2

WGK catalog number Incident regulation

**Information on working limitations** 

Further regulations, limitations and legal requirements

### **Denmark**

Further regulations, limitations and legal requirements

### **Hungary**

Further regulations, limitations and legal requirements

#### **Great Britain**

Further regulations, limitations and legal requirements

#### **Switzerland**

Contents of VOC [%]

~ 74 %

Further regulations, limitations and legal requirements

#### <u>USA</u>

Further regulations, limitations and legal requirements Federal Regulations State Regulations

### Canada

Further regulations, limitations and legal requirements

### 15.2 Chemical Safety Assessment

### **SECTION 16: Other information**

### **Further information**

Hazard statements (CLP) H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information**

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

#### Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### Reason of change

#### **Additional information**

 Article No.
 Issue date:
 09.12.20

 Version
 5.1 ( 09.12.20 )
 Page
 9/ 9

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.