

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

according to Regulation (EC) No. 1907/2006 (REACH)

.

50 064 - Dammar varnish, mat								
Article No.	50064		Issue date:	09.12.20				
Version		5.1 (09.12.20)	Page	1/ 9				
	SECTION 1: Identification of the substance/mixture and of the							
		company/unde	ertaking					
1.1 Product ic	dentifier							
Trade name Name INCI	50 064 - Damı	nar varnish, mat						
Name Ph. Eur. REACH registra UFI	ation No. UFI: U7NF-D469	9-E00G-KN0U						
		substance or mixture and uses a	dvised against					
Gener	ral use Products for cre	ation of art.						
lices	advised against							
	-							
<u>1.3 Details of</u>	the supplier of the safe H. Schmincke & Otto-Hahn-Stras D-40699 Erkratl Tel +49 (0) 211 Fax +49 (0) 211 info@schmincke www.schmincke	Co. GmbH & Co. KG see 2 - 2509 - 0 L - 2509 - 479 .de						
	Schmincke-lab: mo-th 8.00-16.30, fr 8.00-13.30 tel. +49 (0) 211-2509-474 labor@schmincke.de							
<u>1.4 Emergenc</u>	cy telephone number							
	Emergency Information	Emergencycall Berlin +49 30-30686700 (24/7 counseling in g	erman and english)					
		SECTION 2: Hazards	identification					

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aquatic Chronic 2; H411 Toxic to aquatic life with long lasting effects. Asp. Tox. 1; H304 May be fatal if swallowed and enters airways. Flam. Liq. 3; H226 Flammable liquid and vapour. STOT SE 3; H335 May cause respiratory irritation. STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling









Signal word

Danger

Hazard statements

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No. /ersion	50064 5.1 (09.12.20)	Issue date: Page	09.12.20 2/ 9
		raye	2, 0
	H411 Toxic to aquatic life with long lasting effects.		
<u>Safety precautions</u>	 P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and ot smoking. P260 Do not breathe vapours. P273 Avoid release to the environment. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/do P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce von P303+P361+P353 IF ON SKIN (or hair): Take off immediately all conskin with water/or shower. 	ctor/ niting.	
Hazard components	for labelling		
<u>Text for labelling (Cl</u>	<u>.P)</u> Repeated exposure may cause skin dryness or cracking. (EUH066)		

2.3 Other hazards

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

White spirit Dammar resin wax CAS-Number EINECS / ELINCS / NLP EU index number Customs tariff number REACH registration No. RTECS-no. Hazchem-Code CI-Number

3.2 Mixtures

 Substance 1

 solvent naphtha (petroleum), light, aromatic: 50 - <75%</td>

 CAS: 64742-95-6

 REACH: 01-2119455851-35

 Aquatic Chronic 2; H411 / Asp. Tox. 1; H304 / -; EUH066

 / Flam. Liq. 3; H226 / STOT SE 3; H335 / STOT SE 3;

 H336

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

In case of inhalation

Provide fresh air. Seek medical attention if problems persist.

according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No.	50064		Issue date:	09.12.20
Version		5.1 (09.12.20)	Page	3/9

In case of skin contact

Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 10 - 15 minutes. Seek medical attention if irritation persists.

After swallowing

Rinse mouth with water. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Extinguishing media which must not be used for safety reasons

strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes, and clothing.

6.2 environmental precautions

Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Collect spilled material using paper towels and dispose.

Additional information

6.4 Reference to other sections

Dispose of waste according to applicable legislation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Precautions against fire and explosion

No special measures are required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Hints on joint storage Storage class Further details Protect from frost and exposure to sun.

7.3 Specific end use(s)

according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No.	50064		Issue date:	09.12.20
Version	5	.1 (09.12.20)	Page	4/9

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

64742-95-6

solvent naphtha (petroleum), light, aromatic

DEU WEL	50,000	mg/m³	2(II); AGS
---------	--------	-------	------------

DNEL overview 64742-95-6

2	1742-95-6 solvent	naphtha (petroleum), light,	aromatic	
	DNEL worker	Long-term - inhalation, system	150,00000	mg/m³
	DNEL worker	Long-term - dermal, local effe	25,00000	mg/kg bw/day
	DNEL Consumer	Long-term - oral, systemic eff	11,00000	mg/kg bw/day
	DNEL Consumer	Long-term - inhalation, system	32,00000	mg/m³
	DNEL Consumer	Long-term - dermal, systemic e	11,00000	mg/kg bw/day

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection must be worn whenever the WEL levels have been exceeded. Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Nitrile rubber

Layer thickness > 0,35 mm

Breakthrough time > 480 min

Ultranitril 492 - MAPA GmbH, Industriestraße 21-25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EWG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves. This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided.

Eye protection

Goggles

Body protection

Wear suitable protective clothing. Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1 information	on basic physical and che	emical properties				
Form	liquid					
Colour	yellowish, cloudy					
Odour	weak aromatic					
		min	max			
Initial boiling p	oint and					
boiling range						
Melting point/f	reezing point					
Flash point/flas	sh point range	~ 40 °C				
Flammability						
Ignition temper	rature					
Auto-ignition te	emperature					
Explosion limits	5					
Refraction inde	x					
PH						
Viscosity						
Viscosity		10 mm²/s	12 mm²/s	40 °C		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Aı	rticle No.	50064				Issue date:	09.12.20
Ve	ersion	5.1 (09.12.20)			Page	5/9
	Vapour pressure						
	Density			0,84 g/ml	20 °C		
	Partition coefficient: n-e	octanol/water					

Danger of explosion

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

Product is stable under normal storage conditions.

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from frost and exposure to sun.

10.5 Incompatible materials

strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous vapours may form during fires.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological tests

64742-95-6

solvent naphtha (petroleum), light, aromatic

oral	LD50	Rat	>	2000,00000	mg/kg	-
inhalative	LC50	Rat	>	10,20000	mg/L	(4h)
dermal	LD50	Rat	>	2000,00000	mg/kg	-

Acute toxicity

No data available

In case of inhalation

No data available

After swallowing

No data available

In case of skin contact

No data available

After eye contact

No data available

Practical experience

General remarks

SECTION 12: Ecological information

12.1 Toxicity

Ecotoxicological effects

solvent naphtha (petroleum), light, aromatic 64742-95-6

LC50	fish		9,20000	mg/L	(96h)
EC50	Algae	>	2,60000	mg/L	(72h)

according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No. Version	50064	50064 5.1 (09.12.20)			09.12.20 6/ 9
	EC50	Daphnia magna (Big water flea)	3,20000	mg/L	(48h)

Aquatic toxicity

No data available Water Hazard Class WGK catalog number General information

12.2 Persistence and degradability

Further details

Product is partially biodegradable. Oxygen demand

2

12.3 Bioaccumulative potential

Bioconcentration factor (BCF) Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number

080111 080111* waste paint and varnish containing organic solvents or other dangerous substances **Recommendation**

Contaminated packaging

Waste key number Recommendation

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Additional information

SECTION 14: Transport information

14.1 UN number

1263

14.2 UN proper shipping name

ADR, ADNPaint related materialIMDG, IATAPAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR, ADN	3
IMDG	3
IATA	3

14.4 Packing group

 \mathbf{III}

14.5 Environmental hazards

Marine Pollutant - IMDG

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No. Version	50064 5.1 (09.1	2.20)	Issue date: Page	09.12.20 7/ 9
Marine Pollutant - ADN	i	Yes		
14.6 Special precautio	ns for user			
Land transport (ADR)	/RID)			
Code: ADR/RID		F1		
Kemmler-number		30		
Hazard label ADR		3		
Limited quantities		5L		
Contaminated packagi		P001 - IBC03 - LP01 - R001		
Contaminated packagi		PP1		
Special provisions for p		MP19		
Portable tanks: Instrue		T2		
Portable tanks: Special	l provisions	TP1 - TP29 LGBF		
Tank coding Tunnel restriction		D/E		
Remarks		D/L		
EQ		E1		
Special provisions		163 - 367 - 650		
<u>Sea transport (IMDG</u>)			
EmS		F-E, S-E		
Special provisions		163 - 223 - 367 - 955		
Limited quantities		5L		
Contaminated packagi	ng: Instructions	P001 - LP01		
Contaminated packagi	ng: Special provisions	PP1		
IBC: Instructions		IBC03		
IBC: Provisions		-		
Tank instructions IMO		-		
Tank instructions UN		T2		
Tank instructions Spec		TP1 - TP29		
Stowage and segregat		category A		
Properties and observa	ations			
Remarks				
EQ		E1		
<u>Air transport (IATA-D</u>	<u>DGR)</u>			
Hazard		Flammable Liquid		
Passenger		355 (60L)		
Passenger LQ		Y344 (10L)		
Cargo		366 (220L)		
ERG		3L		
Remarks				
EQ		E1		
Special Provisioning		A192		
14.7 Transport in bulk	according to Annex II	of MARPOL 73/78 and the IBC Code		

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Europe

Contents of VOC [%] **Contents of VOC** [g/L] Further regulations, limitations and legal requirements

according to Regulation (EC) No. 1907/2006 (REACH)

50 064 - Dammar varnish, mat

Article No.	50064		Issue date:	09.12.20
Version		5.1 (09.12.20)	Page	8/9

Germany

Storage class Water Hazard Class 2 WGK catalog number Incident regulation Information on working limitations Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%] $\sim 74 \%$ Further regulations, limitations and legal requirements

<u>USA</u>

Further regulations, limitations and legal requirements Federal Regulations State Regulations

<u>Canada</u>

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

Hazard statements (CLP)H226Flammable liquid and vapour.H304May be fatal if swallowed and enters airways.H335May cause respiratory irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.

Further information

This information is abased on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information

Article No.		Issue date:	09.12.20
Version	5.1 (09.12.20)	Page	9/9

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.