

TECHNISCHES DATENBLATT

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

50 404 AEROSPRAY B72Product name:

- AEROSPRAY B72.

Contains:

- Synthetic resin, alcohol, dimethyl ether, propane/butane.

Basic information:

- Fixative for several painting and drawing techniques based on Paraloid™ B72, a high quality synthetic resin, well-known from restauration (EMA-Copolymer), which is dissolved in alcohol.

Characteristics:

- Crystal clear, colourless
- Very fast drying, thermoplastic and flexible
- Non-yellowing and age-resistant
- On absorbant surfaces a nearly invisible fixation

Handling:

- Fixative for charcoal and pencil (so they can be painted over with oil colours!)
- Final fixative for charcoal, pencil and pastels
- Also suitable as fixative for watercolour, gouache and aqua linoprint colours
- Can also be used as varnish for inkjet prints, art prints and photos
- Suitable as protection of gold leaf and other metallic foils
- Final varnish for oil and acrylic colours when applied in several layers (semi mat – slightly glossy)
- Shake well before use. Spray at room temperature by moving the can from one side to the other and from top to bottom and holding the can at a distance of 30 – 40 cm from the vertically positioned or slightly inclined and completely dry object. (Make the change in spray direction away from the picture!)
- The level of gloss depends in accordance to absorbance of the surface, painting technique and the thickness of the film.
- Sometimes an intermediate fixation of the art work is helpful.
- The subsequent fixing of the surface of a picture produced using materials low in binding agents may cause the colour shade to become significantly darker. Using too much fixative frequently causes a loss of "lightness". The product may also make the support, for example the paper, more transparent.
- The fixative coats normally used in practice give no special UV protection to the paints used! For this reason, we recommend that you use high-quality and lightfast artists' paints / printing inks from the outset as far as possible.
- Any clogged-up spray heads are best cleaned using acetone.
- Store in a cool and dry place.
- Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F).
- Individual pre-tests are required (see footer).

Product labeling:

- Please refer to the individual safety data sheet on our website www.schmincke.de.

SG 15/02/17

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·
Tel.: +49-211-2509-0 · www.schmincke.de · info@schmincke.de

