

SAFETY DATA SHEET

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Isopropanol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cosmetics Solvent Disinfection, pharmaceutical purposes.

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company :

Deffner & Johann GmbH Mühläckerstraße 13 D-97520 Röthlein

 Tel.
 +49 9723 9350-0

 Fax
 +49 9723 9350-25

 E-Mail
 info@deffner-johann.de

1.4. Emergency telephone number: Tel. +49 9723 9350-0 (Mo. - Fr.: 8:00 - 15:00 Uhr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol **Signal word:** Danger

Pictograms:



Hazard statements

H225 H319 Highly flammable liquid and vapour. Causes serious eye irritation.

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020	· ·	Page 2 of 12
H336	May cause drowsiness or dizziness.	
Precautionary statement	ts	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P501	Dispose of contents/container to local/regional/national/international regulations.	
2.2 Other hererde		

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	GHS Classification					
67-63-0	propan-2-ol; isopropyl a	propan-2-ol; isopropyl alcohol; isopropanol				
	200-661-7	603-117-00-0	01-2119457558-25			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336					

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing. First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

4.2. Most important symptoms and effects, both acute and delayed

Headache. Dizziness. Nausea. Intoxication. unconsciousness. dehydration of skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam. In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In use, may form flammable/explosive vapour-air mixture. Concentrated vapours are heavier than air. Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove persons to safety. Remove all sources of ignition. Ventilate affected area. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. (See section 8.)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area. Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Page 3 of 12

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 4 of 12

Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight. Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Protect against: UV-radiation/sunlight. heat. Humidity frost. storage temperature: 15-25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-63-0 propan-2-ol; isopropyl alcohol; isopropanol						
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³		
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³		
Worker DNEL,	long-term	dermal	systemic	888 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day		
Consumer DNE	EL, long-term	dermal	systemic	319 mg/kg bw/day		

PNEC values

CAS No	Substance		
Environmental compartment		Value	
67-63-0 propan-2-ol; isopropyl alcohol; isopropanol			
Freshwater		140,9 mg/l	
Freshwater (intermittent releases)		140,9 mg/l	
Marine water		140,9 mg/l	
Freshwater sec	liment	552 mg/kg	

according to Regulation (EC) No 1907/2006

Isopropanol

	Daga

Revision date: 16.03.2020	Page 5 of	12
Marine sediment	552 mg/kg	
Secondary poisoning	160 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

8.2. Exposure controls









Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Eve/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated) In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Skin protection

Wear fire/flame resistant/retardant clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	colourless	
Odour:	Alcohol	_ / // /
		Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point:	-89 °C	
Initial boiling point and boiling range:	82 (Isopropyl alcohol.) °C	ASTM D 1078
Flash point:	12 °C	ASTM D 56
Sustaining combustion:	No data available	
Explosive properties Vapours can travel considerable distar	nces to a source of ignition where they can ignite, flas	sh back, or explode.
Lower explosion limits:	2,0 (Isopropyl alcohol.) vol. %	
Upper explosion limits:	12,0 (Isopropyl alcohol.) vol. %	
Ignition temperature:	425 (Isopropyl alcohol.) °C	
Decomposition temperature:	not determined	
Oxidizing properties none		
Vapour pressure: (at 20 °C)	43 (Isopropyl alcohol.) hPa	
Density:	0,786 g/cm³	
Water solubility:	miscible.	
Solubility in other solvents not determined		
Partition coefficient:	log Kow: 0,05	
Viscosity / dynamic: (at 20 °C)	2,5 mPa·s	
Viscosity / kinematic: (at 25 °C)	2,66 mm²/s	ASTM D 445
Flow time:	not determined	
Vapour density:	not determined	
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	not determined	
2. Other information		
Solid content:	not determined	

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 7 of 12

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard! In use may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis. amines. aldehydes.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol									
		LD50 mg/kg	5840	Rat	ECHA Dossier					
		LD50 mg/kg	> 5000	Rabbit	ECHA Dossier					

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Drying-out effect resulting in rough and chapped skin.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

propan-2-ol; isopropyl alcohol; isopropanol (CAS-No.: 67-63-0):

OECD Guideline 471 (Bacterial Reverse Mutation Assay) = negative., AllgK267153: ECHA Dossier; OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) = negative., Literature information: ECHA Dossier; No indications of human carcinogenicity exist., Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 415 (One-Generation Reproduction Toxicity Study); Species: Rat ; Result: NOAEL = 853 mg/kg; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: (oral.) OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rabbit ; Result: NOAEL = 480 mg/kg; Literature information: ECHA Dossier

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

propan-2-ol; isopropyl alcohol; isopropanol (CAS-No.: 67-63-0):

Chronic inhalative toxicity (Rat): NOAEC = 5000 ppm (OECD 451), Literature information: ECHA Dossier

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 8 of 12

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
67-63-0	propan-2-ol; isopropyl alc	propan-2-ol; isopropyl alcohol; isopropanol							
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	1800		Scenedesmus quadricauda	ECHA Dossier			
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202		

12.2. Persistence and degradability

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
07-00-0							
01-00-0	EU Method C.5/ EU Method C.6	53%	5	ECHA Dossier			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

Mobile in the soil.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

according to Regulation (EC) No 1907/2006

Isopropanol Revision date: 16.03.2020 Page 9 of			
160305			
100305	WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste		
	Code - used product		
160305	WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste		
	Code - contaminated p		
150110	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by		
	hazardous substances;	hazardous waste	
Contaminated Handle co		he same way as the substance itself.	
SECTION 14: Ti	ransport information		
_and transport (A	ADR/RID)		
14.1. UN num	ber:	UN 1219	
14.2. UN prop	er shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)	
	rt hazard class(es):	3	
14.4. Packing	group:	П	
Hazard label:		3	
Classification		F1	
Special Provis Limited quantit		601 1 L	
Excepted quart		E2	
Transport cate	-	2	
Hazard No:		33	
Tunnel restrict		D/E	
	ble information (land tra quantity: E2	nsport)	
nland waterways	s transport (ADN)		
<u>14.1. UN num</u>	ber:	UN 1219	
<u>14.2. UN prop</u>	er shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)	
<u>14.3. Transpo</u>	rt hazard class(es):	3	
<u>14.4. Packing</u>	group:	II	
Hazard label:		3	
Classification		F1	
Special Provisions:		601	
Limited quantity:		1 L	
	nuty: ble information (inland v quantity: E2	E2 vaterways transport)	

Marine transport (IMDG)

according to Regulation (EC) No 1907/2006

Isopropanol				
Revision date: 16.03.2020		Page 10 of 12		
14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label:	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) 3 II 3			
Marine pollutant: Special Provisions: Limited quantity: Excepted quantity: EmS: Other applicable information (marine tra	NO - 1 L E2 F-E, S-D			
Excepted quantity: E2				
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number:</u>	UN 1219			
14.2. UN proper shipping name:	ISOPROPANOL			
14.3. Transport hazard class(es):	3			
<u>14.4. Packing group:</u> Hazard label:	II 3			
Special Provisions: Limited quantity Passenger: Passenger LQ:	A180 1 L Y341			
Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	E2 353 5 L 364 60 L			
14.5. Environmental hazards ENVIRONMENTALLY HAZARDOUS:	no			
14.6. Special precautions for user See section 8.				
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code not relevant.				
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture			
EU regulatory information				
2010/75/EU (VOC):	not determined			
2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III):	50 % (393 g/l) P5c FLAMMABLE LIQUIDS			
Additional information				

according to Regulation (EC) No 1907/2006

Isopropanol

Revision	date:	16.03.2020
----------	-------	------------

Page 11 of 12

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2019/957) The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. REACH 1907/2006 Appendix XVII, No (mixture): 3, 40

National regulatory information

 Employment restrictions:
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

 Water hazard class (D):
 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out: propan-2-ol; isopropyl alcohol; isopropanol

SECTION 16: Other information

Changes

Rev. 1.00; Neuerstellung 22.12.2014 Rev. 1,01; 07.01.2015 Rev. 2,0; 08.03.2018 Changes in chapter: 1 - 16 Rev. 3,0; 16.03.2020, Revision, Changes in chapter: 1 - 16

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level d: day(s) EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European LIst of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h: hour LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect concentration NLP: No-Longer Polymers N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) REACH: Registration, Evaluation, Authorisation of Chemicals SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

according to Regulation (EC) No 1907/2006

Isopropanol

Revision date: 16.03.2020

Page 12 of 12

UN: United Nations

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)