

TECHNICAL DATA SHEET

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

Technical Information

Glutolin Glue (Paint Glue)

Binding agent for distemper and lime paints

Application area: *Glutolin L* is suitable as a binder for distempers and lime paints to improve processing and increase wipe resistance. Limescale and cement resistant

Technical Data:

Raw material base:	Methylcellulose
Bulk weight:	approx. 0,45 g/cm ³
pH-Value:	approx. 7
Solubility:	Ready to use in about 20 minutes

Processing: Put the *Glutolin L* into cold, clean water while stirring and continue stirring for a short time. Shake it powerfully again after about 20 minutes. Afterwards can the *Glutolin L* solution be added to prepared lime and chalk slurries. The additional quantity should be approx. 10%.

Strongly absorbent surfaces should be primed with a *Glutolin L* solution before applying the prepared distemper or lime paint

Cleaning of work tools: Clean with cold or warm water.

Estimated Proportions:

for	Glue estimate	Water quantity pro 125-g	kg	125-g- enough for
Pre-Paste	1 : 50	6 l		60 - 80 m ²
wipe-proof wall and ceiling colors	1 : 25	3 l	5 Chalk	40 - 50 m ²
Lime paint finish	1 : 25	3 l	15 lime	85 - 110 m ²

Storage: Please store in the cold and dry place!

Item No.: 2442000

Pack Size: Box à 125 g