deffner & Johann

Supplies for RESTORATION | CONSERVATION | ART HANDLING – SINCE 1880

TECHNICAL DATA SHEET

6321 050 | Paste Adhesive Tape à 50 mm x 200 m

info@deffner-johann.de | +49 9723 9350-0

Die in diesem Produktdatenblatt genannten Spezifikationen dienen nur zur Produktbeschreibung und beziehen sich auf den Zeitpunkt unmittelbar nach der Produktion bzw. Import des Produktes. Sie entsprechen den Angaben des Herstellers. Eine rechtsverbindliche Zusicherung bestimmter Eigenschaften oder der Eignung für einen bestimmten Einsatzzweck kann hieraus nicht abgeleitet werden. Durch unsachgemäßen Transport und / oder unsachgemäße Lagerung können sich Änderungen ergeben. Die Angaben in diesem Produktdatenblatt entbinden den Verarbeiter nicht von eigener Prüfung der Eigenschaften des Produktes und dessen Eignung für die vorgesehene Verwendung.

Storage and processing instructions for wet adhesive tapes

1. General Information

Product name:	Paste Adhesive Tape from brown Kraft Paper
Components:	Unbleached and chlorine-free bleached paper, vegetable glue adhesive coating

2. Physical properties

Water solubility:	20℃ Gum water soluble
Coating:	20℃ fix

3. Transportation, storage and handling

Transportation:	No special protective measures necessary.
Storage:	Normal Storage. Store dry and clean. Store rolls in shrink wrap to prevent moisture exchange with air. For technical reasons, rolls are packed overdried Adhere to the storage temperature, since later behavior during adhesion can change negatively.
Storage temperature:	18 - 23℃
Humidity:	< 65%
Storage class VCI:	LGK 11 (flammable solids)
Handling:	No special measures necessary under normal conditions. Rolls should be air-conditioned 25 hours before processing (overdried packaging), so unpack the daily ration of rolls the day before and deposit them at the packing station. For successful air conditioning, the relative humidity at the packing station must be between 50% and 70%. The best processing results are achieved at a water temperature of 20° to 23°C.

4. Measures in case of fire hazard

Suitable extinguishing agents:	All (Water, Powder extinguisher, CO^2, etc.)
Zusätzliche Hinweise:	Fire protection equipment. Use self-protective mask and protective clothing. Do not pour down in drains, do not pour in sewerage.

First aid:

5. Toxicological data

No toxic effect.

6. Ecology and recycling

No ecotoxic effect. The gum dissolves in water and is biodegradable. If low concentrations are introduced properly, no disturbances in the degradation activity of the activated are to be expected.

Water hazard class:	WGK 0
Disposal instructions:	Recycling or residual material utilization - especially in connection with corrugated cardboard - possible. Landfill or incineration in compliance with local legislation. Packaging can be recycled, contaminated packaging can be recycled, if recycling is not possible, local authority regulations must be observed for disposal.

Hinweis: Die hierin enthaltenen Informationen basieren auf zuverlässige Daten und beziehen sich nur auf speziell in diesem Dokument enthaltenen Angaben.
Diese Leitlinie wurde nach bestem Gewissen erstellt. Änderungen sind vorbehalten.

Stand Nov. 2010